





- NOTES**
- APPROXIMATELY EVERY 10th POST TO BE STRAINED
 - POST TO BE AT 3300mm CENTRES
 - TOP OF ALL POSTS TO BE KEPT IN UNIFORM LINE
 - CONCRETE MIXES FOR:
 - POSTS CLASS 20/0
 - STRAINER POSTS CLASS 20/0
 - FOUNDATION BLOCK CLASS 15/00 CONC.
 - CHAIN LINK TO BE IN GALVANIZED STEEL WIRE
 - STRAINING WIRES TO BE 12 GAUGE GALVANIZED STEEL FLAT WIRES
 - WIRES ON CHAIN TO BE 12 GAUGE GALVANIZED STEEL BARBED WIRE
 - ALL STRUCTURAL OPENING DIMENSIONS TO BE COMPRISED ON SITE BEFORE COMMENCING ANY FABRICATION
 - STRAINING WIRES TO BE PILED TO POST WITH GALVANIZED PEEK-BOLTS 8mm DIA x 60mm LONG
 - WHERE THE POST ENDOUCHES ON PRIVATE LAND THE FENCE SHOULD BE ERRECTED WITH CHAIN POINTING TOWARDS THE SITE
 - ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE STATED
 - C/C = CENTRE TO CENTRE
 - CTS = CENTRES
 - M.S. = MILD STEEL
 - P.C.C. = PRECAST CEMENT CONCRETE

NO.	REVISIONS	BY	DATE	APPROVED
01	ISSUE	BT		
02		BT		
03		BT		
04		BT		
05		BT		
06		BT		

PROJECT
EQUILIZATION FUND PROJECT

Client:
Northern Water Services Board
P. O. Box 405, TO. CO. DUBLIN

Client:
Northern Water Services Board
P. O. Box 405, DUBLIN

Specific Project:

Engineer:
The Technical Services Manager
Northern Water Services Board
P. O. Box 405, DUBLIN

Drawing Title:

FENCE DETAILS

Survised by: G. Wynne	Drawn by: G. Wynne
Checked by: Eng. Noel	Approved by:
Scale: 1:100	Date: June 2017
Job No.:	Sheet:
Project:	DRAWING NO.:

